

# Power Primer

High-quality, anti-rust alkyd primer

## Description: -

Power Primer is an anti-rust protective primer based on high-quality alkyd resins and other special additives.

## Usage: -

- Power Primer is recommended for all metal surfaces to protect them from rust and corrosion.
- Can be used for new or old metal surfaces.

## Advantages: -

- High adhesion
- High surface protection
- Excellent coverage
- High spreading rate
- Ease of use and application
- Available in red & grey color

### Characteristics: At 25°

color	Gray - Red
Solid content by weight	77 %
Solid content by volume	55 %
Density kg/liter	1.55 ± 0.05
Initial setting time	< 2 hours
Final setting time	24 hours
Re-coating time	5 : 6 hours
Spreading rate (Theoretical)	11 : 13 m <sup>2</sup> / liter / 50 m

### Application instructions: -

- Power Primer should be stirred well before use.
- Surfaces should be cleaned well from dust, oils, grease and other contaminations.
- Paint one or two coats of Power Primer according to the surface condition.
- Paint re-coating layer after 5 : 6 hours.
- Power Primer can be coated with any enamel finish such as Power Tal.
- Make sure that the surface temperature above 5° c

**Dilution:** Dilute Power Primer by (5-10 %) using Power Solve3, mineral oil, or turpentine for a suitable consistency.

**Application:** It can be painted with a brush, roller, or spray gun.

### **Safety precautions: -**

- The product should be applied in a well-ventilated area.
- Gloves, protective clothing, and eye goggles should be worn during application.
- Never eat, drink, or smoke during application.
- In case of skin contamination, wash the contaminated area with water and soap.
- In case of eye contamination, immediately wash with abundant lukewarm water and consult a doctor immediately.
- Avoid spilling residues of the product into any watercourse or soil.
- The used tools should be washed immediately after completion with the cleaning solvent Power Solve 1.
- Dispose of product residues or empty containers according to local environmental regulations.

**Packages: -**

[0.8, 3.5 kg]

**Storage: -**

The product should be stored for two years in tightly sealed containers and under appropriate storage conditions.

For more information or inquiries, Visit our website.

[www.Power-cp.net](http://www.Power-cp.net)

**Disclaimer:** The technical data provided herein is accurate and correct as of the publication date and is subject to change without prior notice. The information in this datasheet is not exhaustive. Application conditions should comply with those mentioned in this datasheet. The company is not responsible for any losses resulting from application under differing conditions.

**Edition: 7/2024**

