

Power Road

Ready-to-Use Road Marking & traffic signs coating

Description: -

- Power Road is a one-component solvent-based alkyd road marking and traffic signs coating.
- Power Road is based on synthetic alkyd resins, premium pigments & other special additives.

Usage: -

- Road marking paint for asphalt floors.
- Decorative Paint for kerbs.
- Marking paint for garages, highways, and car parking.
- Directional signs paint on the floor of hospitals, government buildings, factory floors, loading areas, and traffic signs.

Advantages: -

- High resistance to weather conditions.
- Good adhesion for concrete and asphalt surfaces.
- High abrasion resistance.
- Good resistance to chemicals and petroleum oils.
- Ready and easy to use.
- Available in different colors upon request.

Characteristics: At 25°

color	White / Yellow / Black
Density kg/liter	1.40 ± 0.05 for black 1.50 ± 0.05 for white and yellow
Initial setting time	40 : 60 min
Final setting time	2 : 4 hours
Re-coating time	2 : 3 hours
Rate of use (theoretical)	3 : 5 m ² / kg (2 coats 150 : 175 m)

Application instructions: -

- The substrate must be cleaned well, and free from dust.
- An air compressor or sandblaster can do the final cleaning.
- Apply one or more coats depending on the required thickness using a brush, roller, or spray gun.
- Recoating time must be taken into consideration before applying the next layer.
- Used tools should be cleaned with Power Solve 1

Safety precautions: -

- The product should be applied in a well-ventilated area.
- Gloves, protective clothing, and eye goggles should be worn during application.
- Never eat, drink, or smoke during application.
- In case of skin contamination, wash the contaminated area with water and soap.
- In case of eye contamination, immediately wash with abundant lukewarm water and consult a doctor immediately.
- Avoid spilling residues of the product into any watercourse or soil.
- The used tools should be washed immediately after completion with the cleaning solvent Power Solve 1.
- Dispose of product residues or empty containers according to local environmental regulations.

Packages: -

1 kit in volume [Gallon 4 Kg].

[Pail 20 Kg].

Storage: -

The product should be stored for one year in tightly sealed containers and under appropriate storage conditions.

For more information or inquiries, Visit our website.

Power-cp.net

Disclaimer: The technical data provided herein is accurate and correct as of the publication date and is subject to change without prior notice. The information in this datasheet is not exhaustive. Application conditions should comply with those mentioned in this datasheet. The company is not responsible for any losses resulting from application under differing conditions.

Edition: 7/2024

