

# Power X 55

High-quality semi-glossy acrylic plastic paint.

## Description: -

High-quality semi-glossy acrylic paint for exterior and interior use, made from acrylic copolymer resin and special additives, providing excellent coverage and washability.

## Usage: -

New or previously painted concrete, gypsum, and cement walls and ceilings.

## Advantages: -

- Excellent whiteness resistant to yellowing.
- Very good coverage strength.
- High spread rate.
- High adhesion strength and resistance to weather conditions.
- Excellent washability.
- Easy to apply and use.
- Good resistance to chalking..

**Characteristics: At 25°**

color	White / Colored
Density ( g / cm <sup>3</sup> )	1.24 $\pm$ 0.05
Initial setting time	Minimum 45 Minutes
Final setting time	Minimum 24 hours
Second coat	Minimum 8 hours
Rate of use	10 : 15 m <sup>2</sup> / L (for one coat with a dry paint layer thickness of 30 : 40 microns).

**Dilution Rate:** 10 to 15% of the product's weight.

**Application Tools:** Roller, brush, spray gun.

**Application instructions: -**

- The surface to be painted must be clean, dry, and free from dust, grease, oils, or any contaminants that may affect the quality of the paint application.
- Any cracks or roughness in the surface should be repaired, followed by thorough sanding and cleaning before application.
- Apply one coat of Power Sealer, then apply Power Putty (one or two coats depending on the surface condition).
- Apply two coats of Power X 55, ensuring that dilution does not exceed 15% of the product's weight to achieve the appropriate application viscosity.

- For previously painted (old) surfaces, clean the surface thoroughly, remove dust and impurities, and sand the surface—especially oil-based surfaces—to ensure proper adhesion.
- Stir the container well before use.

### **Safety precautions: -**

- The product should be applied in a well-ventilated area.
- Gloves, protective clothing, and eye goggles should be worn during application.
- Never eat, drink, or smoke during application.
- In case of skin contamination, wash the contaminated area with water and soap.
- In case of eye contamination, immediately wash with abundant lukewarm water and consult a doctor immediately.
- Avoid spilling residues of the product into any watercourse or soil.
- The used tools should be washed immediately after completion with water.
- Dispose of product residues or empty containers according to local environmental regulations.

**Packages: -**

The product is available in the following sizes: can, gallon, bucket, and jumbo bucket.

**Storage: -**

The product should be stored for two years in tightly sealed containers and under appropriate storage conditions.

For more information or inquiries, Visit our website.

[Power-cp.net](http://Power-cp.net)

**Disclaimer:** The technical data provided herein is accurate and correct as of the publication date and is subject to change without prior notice. The information in this datasheet is not exhaustive. Application conditions should comply with those mentioned in this datasheet. The company is not responsible for any losses resulting from application under differing conditions.

**Edition: 7/2024**

