

Primer Fast

High-quality, fast-drying primer paint for metal, concrete, and wooden surfaces.

Description: -

Fast Primer: A single-component, fast-drying protective paint based on high-quality modified alkyd resins.

Fast Primer: Features good weather resistance, quick drying, and acts as a protective coating for concrete, wooden, and metal structures (for both indoor and outdoor use).

Usage: -

- Used as a primer for metal surfaces and iron structures.
- Used to protect cement and concrete surfaces.
- Used as a coating for metal tanks.
- Used for painting warehouses and workshops.

Advantages: -

- A primer paint characterized by fast drying and a single-component formula.
- High adhesive strength on various surfaces.
- Exceptional coverage and good spreading rate.
- Features a smooth, high-quality glossy finish.

- Easy to apply and use, whether with a spray gun, roller, or brush.

Characteristics: At 25°

| | |
|---------------------------|--|
| color | Customized |
| Density g/cm ² | 1.4 ± 0.05 |
| Initial setting time | 20 : 35 hours |
| Final setting time | 24 hours |
| Re-coating time | 8 : 10 hours |
| Consumption rate | 5 : 7 m ² / kg (dry film 50 micron) |
| Thinner | Power Solve 4 |

Note: The consumption rate depends on the nature of the surface, paint thickness, application method, and preparation of the surface to be painted.

Dilution Rate: 10% : 20% of the product's weight, depending on the nature of the application.

Tools: Roller, Brush, Spry Gun

Application instructions: -

- The surface to be painted should be thoroughly cleaned of dust, oils, grease, or loose particles, and rust should be removed in the case of metal surfaces.
- Old paint surfaces should be sanded well, and any rust should be removed, followed by cleaning.

- The product should be stirred well before application to achieve a distinctive finish.
- Application should be done according to industry standards, using a brush or roller in both longitudinal and transverse directions, ensuring complete coverage of the surface to be painted or sprayed.
- The second coat, if needed, should be applied after 8 to 10 hours.
- Typically, two coats of Power Primer Fast are applied, ensuring the first coat is completely dry.
- The product can be thinned, if necessary, with Power Solve 4 solvent.

Safety precautions: -

- The product should be applied in a well-ventilated area.
- Gloves, protective clothing, and eye goggles should be worn during application.
- Never eat, drink, or smoke during application.
- In case of skin contamination, wash the contaminated area with water and soap.
- In case of eye contamination, immediately wash with abundant lukewarm water and consult a doctor immediately.
- Avoid spilling residues of the product into any watercourse or soil.
- The used tools should be washed immediately after completion with the cleaning solvent Power Solve 1.
- Dispose of product residues or empty containers according to local environmental regulations.

Packages: -

[4, 20, 200 kg]

Storage: -

The product should be stored for two years in tightly sealed containers and under appropriate storage conditions.

For more information or inquiries, Visit our website.

www.power-cp.net

Disclaimer: The technical data provided herein is accurate and correct as of the publication date and is subject to change without prior notice. The information in this datasheet is not exhaustive. Application conditions should comply with those mentioned in this datasheet. The company is not responsible for any losses resulting from application under differing conditions.

Edition: 7/2024

